

GENERAL RULES

1. All drivers under 16 must have written permission from a parent or guardian and **MUST** wear a helmet.
2. Drivers are to conduct themselves appropriately, no profanity, or alcohol or drugs are to be on park property at **ANY TIME**.
3. Drivers are responsible for picking up their winnings after the class.
4. A drivers meeting will be held before the event begins.
5. Drivers may bump up in horsepower classes.
6. What is done for ONE driver will be done for ALL drivers.
7. Drivers may be asked to assist in working the track to keep things moving smoothly and quickly.
8. NO pets are permitted.
9. No individuals are to be on the track at any time during the pull unless they are working.
10. **SAFETY IS PRIORITY ON AND OFF THE TRACK.**
11. ALL twin cylinder tractors **MUST** pull in the twin cylinder class.

ENGINE SET-UP

1. Stock garden tractor engines 0-25 hp. 3-cylinder diesel permitted.
2. Stock garden tractor must have stock engine parts: cam, crank, carb, points, coil, starter and must have come in a residential garden tractor.
3. Permitted engine modifications:
 - A. .030 over bore max.
 - B. Head may be milled for clean up
 - C. May be ported and polished
 - D. Electric fuel pump
 - E. Throttle pedal instead of manual cable
 - F. Can use copper head gasket
4. Engine must have working governor and air cleaner.
5. Pump gas and diesel fuels only. **NO** alcohol fuels permitted. Cam 2 is permitted.
6. All exhaust, header pipes must be 90 degrees straight up.
7. No carb adaptor spacers or velocity stack. Must have carb for that engine.
8. **THESE ARE THE ONLY MODIFICATIONS ALLOWED, ALL OTHERS ARE NOT PERMITTED!!!!**

HITCH SET-UP

1. Hitch height will be 12 inches to the top of the hitch.
2. All hitches must be stationery when pulling in all directions with a minimum of 1 1/2 inch hole. 3/8 inch thick steel or 1/2 inch aluminum plate.

TRACTOR SET-UP

1. All tractors must be of garden tractor variety, patented and factory built, **NO HOMEMADE TRACTORS.**
2. All tractors must have a factory hood and grille, the grille may be altered for weight purposes, but must remain stock in appearance.
3. All tractors **MUST** have working brakes.
4. All tractors **MUST** have a seat with a back to stop the driver from sliding off.
5. Smaller air tires are permitted on the front of the tractor within reason.
6. No dual wheels or tire chains are permitted.
7. Rear tires **MUST** be either agricultural tread or turf type. Tires may be sharpened. 0-10 hp max size is 23x10.50-12; 11 hp and up may have a max. tire size of 26-12x12.
8. Fenders: if the tractor came with fenders then they must be on the tractor. Fenders may be altered to lighten or widen.
9. Stock frames only; no homemade frames.
10. Guards and shields; Stock guards and shields are to remain on the tractor. Open clutches, belts and chains must have shields. Shields are to be made from 1/8 steel or 3/16 aluminum minimum.
11. May have support bearings on drive shaft for safety.
12. **NO PROFESSIONAL PULLING TIRES.**

WEIGHT SET-UP

1. All weights must be securely fastened.
2. Weight brackets specifications:
 - A. No part of the weight or bracket can exceed 72 inches from the center line of the rear axle forward to the front of the tractor.
 - B. No part of the weight or bracket can exceed 18 inches from the center of the rear axle backwards to the rear of the tractor.
 - C. No part of the weight or brackets can exceed 24 inches from center line of the rear axle upwards.
 - D. No part of the weight or brackets can exceed 12 inches past the outer edge of the sidewall of the rear tire.
 - E. All weights must be in boxes, brackets, or secured to the tractor, not loose or sitting.
 - F. No part of the weight or bracket can interfere with hook up.

WHEELIE BARS

1. All tractors **MUST** have wheelie bars. They must be built to withstand the **TOTAL** weight of the tractor for each side.
2. Wheelie bars can **NOT** interfere with the hitch hook up area.
3. They must be a minimum of 5 inches back from rear edge of the tire to the center of the wheel (4 in. diameter x 1 inch wide min. or a steel plate 3 in. x 3 in. x 1/8 in. thick).
4. No more than 5 inches from surface to point of contact of the wheel or plate.

DRIVING AND TRACK RULES

1. Pullers must start from a tight chain.
2. Drivers should have the tractor out of gear and hands off the controls when hooking.
3. Know your position. Calls will be made across the loud speaker who is pulling and who is to follow. This helps to keep the pull moving faster.
4. All drivers must sign in prior to starting a class.
5. All tractors must be weighed in and measured prior to the class starting.
6. All tractors are subject to random weight and height checks. If changing air pressure in tires you **MUST** recheck the height of your hitch.
7. Drivers are to weigh out of each class, Weight can be under **NOT** over.
8. No parking on the scales.
9. Drivers are to **WATCH** the flag person. Track crew makes the call. **DRIVERS ARE TO STOP WHEN INSTRUCTED. DIGGING HOLES/ PAWING WILL NOT BE PERMITTED.**
10. Weights may be moved on the tractor for better traction during the pull but no weight can be added.
11. If one of the first two drivers can not make a full pull the class will be restarted and weight removed. **Dead weight pulls only. Transfer sled will have a floating finish line.**
12. **KEEP HANDS OFF FENDERS, AWAY FROM TIRES AND OFF THE BACK OF THE SEAT!!!**
13. Drivers are to remain in seat. The seat must have a back to keep the driver from sliding off the back of the tractor, One hand on the steering wheel at all times. Leaning from side to side is permitted.
14. **NO FISH TAILING OR JERKING FROM SIDE TO SIDE.** This may cause the tractor to roll.
15. Ropes are set up on the side for boundaries. If a tractor crosses or touches the rope the driver is **DISQUALIFIED. EXCEPTION:** if pulling and the front-end is up and crosses the rope as long as the tractor stops inside the rope the pull will be accepted. **DRIVERS ARE RESPONSIBLE FOR STAYING INSIDE THE ROPES.**
16. **DRIVERS WILL BE DISQUALIFIED IF ANY PART OR WEIGHT FALLS OFF THE TRACTOR DURING THE PULL OR STOPPING THE TRACTOR AS LONG AS YOU ARE HOOKED TO THE SLED.**
17. **One award per tractor, per class.**
18. Two drivers per tractor per class is permitted.

MODIFIED RULES

1. Front weights must **NOT** exceed 72 inches from rear axle.
2. Rear weights must **NOT** exceed 18 inches behind the rear axle.
3. 10 hp modifieds may run any type of rear tire, but **NOT** to exceed 23 x 10.50 x 12
4. **AFTER MARKET BLOCKS ARE NOT PERMITTED!!!** (10 hp tractors must use a stock single-cylinder 10 hp block; 14 hp tractors must use a 14 hp stock single-cylinder block, etc.)
5. 14,16 and 25 hp may use any type of tire but can not exceed 26 x 12 x 12.
6. All engines must have been available in a residential garden tractor.
7. **NO HOMEMADE TRACTORS**
8. **ALL TRACTORS MUST HAVE A WORKING SAFETY KILL SWITCH!!!!!!**
9. **ALL** drivers **MUST** wear a helmet.
10. All general tractor set-up rules apply.
11. All hitches will be 12 inches in all classes.
12. Steel fly-wheels are recommended.
13. 52" Wheel Base Max.
14. A stock appearing Kohler type carburetor must be used if other than stock for the model engine being used. Choke may be removed. Single carburetor only. Air restricting venturi must be in stock position and carburetor not to be larger diameter than 1.200". Air controlled by butterfly in stock position in carburetor, no slides, no injection, naturally aspirated only. No air entering after 1.200" restriction. Venturi must be round in shape.

WHEEL BASES

1. **50" Wheel base on ALL Stock tractors**
 2. **52" Wheel base on ALL Modified tractors**
-